

Speed Limits and Statistics

MTE User Manual - Report Profiles

3.21 May 2009



Posted Speed Limit

The Posted Speed Limit (PSL) is the speed limit at the site where data was collected, and is used as the basis for speed statistics such as the number of speeding vehicles. The PSL can be settings are located on the **Speed** page of the Advanced Profile options.

010	0	0 Add bin Delete bin 21 of 30		#	Scale (%)	Offset (km/h)	Name	-
✓ 20-30 ✓ 30-40	0	0 Din multiplier		0	100	0	PSL	
✓ 40-50 ✓ 50-60	0	Speed links (km/h)		01	100	5	PSL+5	=
✓ 60-70 ✓ 70-80	0	Scale (3) Offset (km/h) Name A Scale (3) 0 PSL		<u>60</u> 2	110	0	PSL+10%	
✓ 00-90 ✓ 90-100	0 1	1 100 5 PSL+5 #		03	100	0		
✓ 100-110 ✓ 110-120	0	G 3 100 0		60 4	100	0		
✓ 120-130 ✓ 130-140	0	ES 100 0		605	100	0		
140-150 150-160	0	End posted served limit from data		606	100	0		
160-170		60 Posted speed limit		Ā-	100	0		
✓ 100-190 ✓ 190-200	0 -	Speed statistics (km/h) Percentile 2 Pace	111	🔽 Get	posted speed I	limit from data		

Speed limits

The PSL can be automatically derived from the tagged datasets. With the **Get posted speed limit from data** option checked, MCReport will scan the **Description** field of the tagged datasets' headers, looking for a PSL in the following form:

- Must be enclosed in angle brackets < >
- Default is km/h. Append an 'm' or 'M' for mph.
- The PSL can appear anywhere in the description, but other angle brackets cannot be inserted when using this feature.

Example Site	Descriptions
km/h	mph
Hay St <60>	<40 mph> Speed test, Euston Road
<60km/h> Hay Street	ACPO test, Harrow Road <40m>
Hay St, <50 km/h> study	Harrow Road, PSL=<40 MPH>

With this option checked, if MCReport does not find a valid speed limit, or there are multiple tagged datasets with conflicting PSLs, the PSL will be set to zero.

The best time to insert the PSL into the Description field is when a RSU is setup, and when creating Site Lists. For existing datasets the PSL can be inserted into the description using the **Transform data file** feature in MCReport's File Tree.

When the automatic PSL option is unchecked, the PSL can be manually entered in the **Posted speed limit** box provided.

Speed Limits

The Speed limits list allows up to 10 additional speed thresholds to be set based on the PSL, using

the formula (PSL * Scale/100) + Offset. The Scale column is a percentage, and Offset can be a positive or negative amount, in the same units as the PSL. Each additional limit can also be uniquely named.

To edit a speed threshold, simply double-click. Note that the first limit in the list is always the PSL, and cannot be changed.

Speed limits	×				
Limit = PSL * Scale/100 + Offset					
110	Scale (percent)				
0	Offset km/h				
PSL+10%	Name				
	OK Cancel				

Editing speed limit thresholds

For example, given a PSL of 80, a scaling percentage of 110 will result in a speed threshold of 88. For a simple offset, leave the scaling percentage at 100 and use the Offset field.

Thresholds which are left as the same as the PSL (100% + 0) will not be displayed in reports.

Speed Percentiles and Pace

The **nth speed percentile** is the speed below which \mathbf{n} % of vehicles were travelling. For example, the commonly used 85th percentile is the speed below which 85% of vehicles were travelling. MCReport supports two speed percentiles, which can be set in 5% steps.

The **speed pace** is a continuous band of speeds **n km/h** or **mph** wide that contains the largest number of vehicles. The speed pace is a measure of the dispersion of speeds at a site, based on the number and percentage of vehicles within the pace. The speed pace can be set in 5 km/h or mph increments.

ldd bin Delete bin 21 of 30 ultiplier				
ulpier				
suliplier				
nh)				
r(%) Offset(km/h) Name	A 10	Speed statistics (km/h)	J	
0 PSL		opeed statistics (tanking	1	
5 PSL+5		Percentile 1	Percentile 2	Pace
0 PSL+10%			1 OFOOT KIID E	1 400
0		85 -	95 -	20
0		00 Ŧ		20
0				
0	· /			
d second limit from data				
report and the second second				
nied speed with				
cs (\$10,\$1)				
Percentile 2	Pace			
cale 00 10 10 10 10 10 10 10 10 10 10 10 10	Other (Junch) Name 00 0 PSL 00 5 PSL S 10 0 PSL S 10 0 PSL S S 10 0 PSL S S 10 0 PSL S	Cole (3) Name 0 0 PSL 0 5 PSL 0 0 PSL 0 PSL PSL	Cole 173 Name 0 0 PSL 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 <td>Colored Subsystems of the second seco</td>	Colored Subsystems of the second seco

Speed statistics

For example, given a speed histogram, the 85th speed percentile will be a vertical line, with 85% of vehicles to the left. A 20km/h pace is a band 20km/h wide that contains the most vehicles.



Conceptual speed histogram examples showing 85th percentile, and 20km/h pace

Speed Statistics Block

Many speed-related reports combine the above speed limits and statistics into a compact block. An example of the form of this is provided below.

Vehicles = 125765
Posted speed limit = 80 km/h, Exceeding = 84352 (67.07%), Mean Exceeding = 86.88 km/h
Limit 1 (PSL+10%) $(80 * 110\%) + 0 = 88 \text{ km/h}$, Exceeding = 27223 (21.65%)
Maximum = 174.7 km/h, Minimum = 0.0 km/h, Mean = 83.2 km/h
85% Speed = 90.0 km/h, 95% Speed = 95.8 km/h, Median = 82.4 km/h
20 km/h Pace = $73 - 93$, Number in Pace = 107015 (85.09%)
Variance = 60.72 , Standard Deviation = 7.79 km/h

www.metrocount.com

Copyright© 1991, 2009 Microcom Pty Ltd. All rights reserved. MetroCount, Traffic Executive, MCSetup, MCSetLite, MCReport, MCTools, Microcom and Microcom Pty Ltd, and the MetroCount and Microcom Pty Ltd logo, are trademarks of Microcom Pty Ltd. All other trademarks are the property of their respective owners. Other Microcom intellectual property including Patents and designs may be protected by international law. The furnishing of this software, the accompanying product or any related documentation or materials does not give you any license to this intellectual property.